



BIT GUIDES AND RIVETING HEADS



Bit Guides for Screwdrivers

Bit Guides are the best accessory to help long bits, wire thread insert and riveters keep the correct perpendicular position. They can be installed on inline screwdrivers model PLUTO3, PLUTO6, PLUTO10, PLUTO15 and on any inline KBL:

- RIV HD1, 8 mm hole (code 010180) for PLUTO3D, PLUTO6D, PLUTO10D/N, PLUTO15D/N
- RIV HD2, 8 mm hole (code 010181) for KBL30FR and KBL40FR, also for models with signals (KBL..FR/S) and autoreverse (KBL..FR/AR)
- RIV HD3, 3 mm hole (code 010182) for PLUTO3D, PLUTO6D, PLUTO10D/N, PLUTO15D/N
- RIV HD4, 3 mm hole (code 010183) for KBL04FR and KBL15FR, also for models with signals (KBL..FR/S) and autoreverse (KBL..FR/AR)
- RIV HD5, 3 mm hole (code 010184) for KBL30FR and KBL40FR, also for models with signals (KBL..FR/S) and autoreverse (KBL..FR/AR)

Riveters and wire thread inserts may require the screwdriver to automatically start a loosening operation once the torque has been reached. This is easily achieved via the "autoreverse" feature, which is available either on PLUTO drivers (by selecting the proper settings on the EDU2AE control unit) and brushless screwdrivers, specifically models KBL..FR/AR (see page 14).

RIV HD bit guides are supplied standard with 3 mm hole or 8 mm hole with roller bearings (special dimensions can be made upon request).

ACC SERIES

ACC Screwdrivers

ACC screwdrivers with shut off torque control through mechanical clutch are direct plug-in tools with built-in PCB for automatic cut off and AC to DC rectifier. They are ideal for applications where portability is needed to minimize costly set-up time. ACC models have the unique feature of selectable push to start or push and lever start.

To select the working mode just slide the switch located by the start lever.



REVERSE
SWITCH



TORQUE ADJUSTING
NUT COVER

Model	Code	Torque Nm	RPM max	Weight kg	Dimensions mm	Controller
ACC2210	141910	0,2-1,0	950	0,75	255x35	230 VAC
ACC2220	141920	0,7-2,0	950	0,80	255x35	230 VAC
ACC2222	151222	0,9-2,0	2400	0,85	265x38	230 VAC
ACC2230	151930	1,0-3,0	950	0,85	265x38	230 VAC
ACC2245	151945	1,0-4,5	450	0,85	265x38	230 VAC

Optional Lock-out Cover & Nut Assembly available for all ACC models (code 219011).

WESTEC® - Sales & Services In India

Office No. 12, 1st Floor, Hermes Atriam,
B Wing, Plot 57, Sector - 11,
CBD Belapur, Navi Mumbai - 400614

Mob: 98210 32720 | Tel:+91-22-2756 6533
Telefax: +91-22-2756 6534 | Website- <http://westec-india.com>
Email: team@westec.in