


Interchangeable Head Micrometer Adjustable

CCM

Series

- Incredible Versatility! Accepts well over 100 interchangeable heads, as well as custom heads and extensions, and offers micrometer torque adjustment!
- The +/- 4% Indicated Value Accuracy meets or exceeds ASME B107.300 - 2010, AS 28431 and ISO 6789.
- Fast adjustment—takes the fewest rotations of any tool to reach full scale!
- Includes FREE calibration certificate from our ISO/IEC 17025 Accredited Laboratory.
- Excellent audible and tactile impulse when set torque achieved.
- Unique dovetail design transmits the load at right angle from the wrench to the head; exceptional strength and rigidity of connection.
- The pin lock assures positive head connection, yet permits head changeover in seconds!



Part No.	Model	Torque Capacity	Steps of Graduations	A (in.)	B (in.)	C (in.)	D (in.)	Weight (lbs)
869769	CCM 50 I MG	10 in lb-50 in lb	1 in lb	10 1/8	3/4	17/32	15/16	0.5
869765	CCM 150 I MG	30 in lb-150 in lb	2 in lb	10 1/64	3/4	17/32	15/16	0.5
869773	CCM 200 I MG	40 in lb-200 in lb	2 in lb	10 1/64	3/4	17/32	15/16	0.5
869763	CCM 600 I MG	100 in lb-600 in lb	5 in lb	13 17/32	1	17/32	15/16	1
869766	CCM 750 I MG	150 in lb-750 in lb	5 in lb	13 17/32	1	17/32	15/16	1
869764	CCM 1200 I MG	200 in lb-1200 in lb	10 in lb	16 29/32	1 1/4	17/32	15/16	1.1
869762	CCM 1800 I MG	300 in lb-1800 in lb	10 in lb	16 9/16	1 1/4	17/32	15/16	1.3
869770	CCM 75 MG	15 ft lb-75 ft lb	1/2 ft lb	13 41/64	1	17/32	15/16	1
869771	CCM 150 MG	30 ft lb-150 ft lb	1 ft lb	17 7/64	1 1/4	17/32	15/16	1.3
810335*	CCM 300 MG	50 ft lb-300 ft lb	2 1/2 ft lb	25 23/32	1 3/4	48/64	2	6.5
810772*	CCM 400 MG	80 ft lb-400 ft lb	5 ft lb	35	1 3/4	48/64	2	8.3

Part No.	Model	Torque Capacity	Steps of Graduations	A (mm)	B (mm)	C (mm)	D (mm)	Weight (kg)
869784	CCM 6 Nm MG	1 Nm-6 Nm	.1 Nm	259.36	19.05	13.49	23.81	0.2
869785	CCM 20 Nm MG	4 Nm-20 Nm	.2 Nm	257.63	19.05	13.49	23.81	0.2
869786	CCM 100 Nm MG	20 Nm-100 Nm	0.5 Nm	347.39	19.05	13.49	23.81	0.5
869787	CCM 200 Nm MG	40 Nm-200 Nm	1 Nm	426.43	31.75	13.49	23.81	0.6
810788*	CCM 400 Nm	75 Nm-400 Nm	2.5 Nm	649.93	50.6	17.02	50.93	3
810794*	CCM 600 Nm	100 Nm-600 Nm	5 Nm	903.92	50.6	17.02	50.93	3.8

*Wrenches calibrated for use with heads having 3 7/8" (98.4mm) common centerline. On request wrenches can be calibrated for 1 7/16" (36.5mm) centerline.

WESTEC[®] - Sales & Services In India

Office No. 12, 1st Floor, Hermes Atrium,
B wing, Plot 57, Sector – 11,
CBD Belapur, Navi Mumbai – 400 614

Mob: 9821 0327 20 | Tel:+91-22-2756 6533
Telefax: +91-22-2756 6534 | Website - <http://westec-india.com/>
E-mail: westecnavimumbai@vsnl.net